

# Si-COAT<sup>®</sup> 532<sup>™</sup> REMARKABLE<sup>®</sup> LOW VOC SPRAY GRADE ANTI-GRAFFITI PROTECTIVE COATING

Issue Date (D/M/Y): DRAFT - 05/11/2018 Replaces (D/M/Y): 16/08/2015

Page 1 of 10

I. Identification	
Product Identifier:	Si-COAT® 532™ Remarkable° Low VOC Spray Grade Anti-Graffiti Protective Coating
Use:	Polysiloxane coating.
Manufacturer:	CSL Silicones Inc.
	144 Woodlawn Road West, Guelph, ON, N1H 1B5
	Canada
Manufacturer Phone:	North America: 1.800.265.2753 Worldwide: +1 519.836.9044
Emergency Phone:	+1 519.836.9044 Monday - Friday, 8:00 A.M 5:00 P.M. Eastern Time Zone, UTC-05:00
Emergency Contact:	Baz Mistry, Laboratory Manager; Farooq Ahmed, R&D Manager
. Hazards Identifica	
GHS Hazard Classification:	Acute Toxicity – Category 4
	Eye Irritant – Category 2
	Reproductive Toxicity – Category 2
	Single Target Organ Toxicity (STOT) Repeated Exposure – Category 2
	Skin Corrosion – Category 2
	Skin Sensitizer – Category 1
GHS Hazard Symbols:	
GHS Signal Word:	Warning Warning
GHS Hazard Statements:	H302 - Harmful if swallowed.
	H315 - Causes skin irritation.
	H317 - May cause an allergic skin reaction.
	H319 – Causes serious eye irritation.
	H361 - Suspected of damaging fertility.
	H373 - May cause damage to organs through prolonged or repeated exposure. Affected organs: cardiovascular/hematological (hematopoiesis).
GHS Precautionary Stateme	ents:
Prevention:	P260 – Do not breathe fumes/mist/vapour/spray.
	P262 – Do not get in eyes, on skin, or on clothing.
	P273 - Avoid release to the environment.
	P280 - Wear protective gloves/protective clothing/eye protection/face protection
Response:	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P305+P351+P338 - IF IN EYES: Rinse cautiously for several minutes. Remove contac lenses, if present and easy to do. Continue rinsing.
	P310+314 - Immediately call a Poison Control Center/doctor and get medical advice/attention if you feel unwell.
Storage:	P403+P233+P235 - Store in a well ventilated place. Keep container tightly closed. Keep cool.
Disposal:	P501 – Dispose of contents/containers to waste in accordance with local and nationa regulations.



ANTI-GRAFFITI PROTECTIVE COATING

Issue Date (D/M/Y): DRAFT - 05/11/2018 Replaces (D/M/Y): 16/08/2015

## SAFETY DATA SHEET

Page 2 of 10

Other Hazards which do not Not applicable. result in GHS classification:

## 3. Composition / Information on Ingredients

Chemical Characterization: Silicone elastomer

## According to Regulation (EC) No. 1272/2008:

Name	CAS No.	EINECS/ ELINCS No.	Reach Registration No.	Conc. (%w/w)	Classification
Butan-2-one-0,0',0"- (methylsilylidyne)trioxime	22984-54-9	245-366-4	01- 2119970560- 38-0007	1 - 5	Skin sensitizer: category 1B - H317 STOT repeated exposure - category 2 - H373
Butan-2-one-0,0',0"- (vinylsilylidyne)trioxime	2224-33-1	218-747-8	01- 211970537- 27	1 - 5	Eye irritant: category 2 - H319 Skin sensitizer: category 1B - H317 STOT repeated exposure: category 2 - H373
3-aminopropyltriethoxysilane	919-30-2	213-048-4	01- 2119480479- 24	1 - 5	Acute toxicity: category 4 - H302 Skin corrosion: category 2 - H315 Skin sensitizer: category 1 - H317
Octamethylcyclotetrasiloxane*	556-67-2	209-136-7	01- 2119529238- 36	0.1 - 0.8	Reproductive toxicity: category 2 - H361

Octamethylcyclotetrasiloxane (D4) is classified under GHS as Reproductive Toxicity - Category 2 (H361 -Suspected of damaging fertility) based on reproductive studies in animals. See Section 11 for further details.

CLP classifications are based on all current available data including from known international organizations. These classifications are subject to revision as more information becomes available.

Ingredients not precisely identified are proprietary or non-hazardous. Values are no product specifications.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentration applicable, are classification as hazardous to health or the environment and hence require reporting in this section

Occupational exposure limits, if available, are listed in Section 8.

## 4. First Aid Information

IF POISONING IS SUSPECTED, immediately contact the poison control center, doctor or nearest hospital. Have the product container, label or Safety Data Sheet with you when calling CSL Silicones Inc., a poison control center or doctor, or going for treatment. Tell the person contacted the complete product name, and the type and amount of exposure. Describe any symptoms and follow the advice given.

- Inhalation: The affected person should be moved to fresh air and made comfortable. Obtain medical attention as a precaution.
- Eye Contact: Do not attempt to remove solids or gums from the eye. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 20 minutes, holding the eyelids open. After 5 minutes, remove contact lenses if present and possible, and continue rinsing. Obtain medical attention immediately.
- Skin Contact: Remove contaminated clothing. Wash gently and thoroughly with water and nonabrasive soap. If symptoms persist, obtain medical attention. Contaminated clothing should be laundered before re-use.

silicones inc.

## Si-COAT<sup>®</sup> 532<sup>™</sup> REMARKABLE<sup>®</sup> LOW VOC SPRAY GRADE

ANTI-GRAFFITI PROTECTIVE COATING

Issue Date (D/M/Y): DRAFT - 05/11/2018 Replaces (D/M/Y): 16/08/2015

#### Page 3 of 10

Ingestion:

Never give anything by mouth if victim is rapidly losing consciousness, is unconscious or convulsing. DO NOT INDUCE VOMITING. Have victim rinse out mouth and drink 8 to 10 oz. (240 to 300 ml) of water or milk to dilute the material in stomach. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Repeat the administration of water/milk. Obtain medical attention immediately.

### Self-Protection of the First Aider:

Use personal protection equipment to avoid contact with the product.

#### Most Important Symptoms/Effects:

At high vapour concentrations, curing by-product has a narcotic action with reversible effects. Prolonged exposure to curing by-product vapours can cause headache, nausea, central nervous system depression, anesthesia and dizziness.

Eye contact: Moderate irritation. Can cause burns.

Dermal contact: Mild irritation; may cause transient reddening of the skin.

Ingestion: Very low toxicity. May cause irritation and obstruction of the gastro-intestinal tract.

Indication of Immediate Medical Attention and Special Treatment Needed:

There is no specific antidote if ingested.

Treat symptomatically.

## 5. Fire Fighting Measures

Suitable Extinguishing Media:

Dry chemical, CO<sub>2</sub>, water spray, chemical foam.

Unsuitable Extinguishing Media:

Do not use water jet as an extinguisher as this may spread the fire.

Specific Hazards:

Hazardous combustion products: carbon dioxide, carbon monoxide, formaldehyde, silicon dioxide, nitrogen oxide.

Advice for Firefighters:

Self-Contained Breathing Apparatus (SCBA) should be used for all indoor fires and any significant outdoor fires. Full protective clothing should be worn at all times.

## 6. Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures:

For non-emergency and emergency responders:

Make sure all personnel involved in the clean-up follow good industrial hygiene practices. A small spill can be handled routinely. Use adequate ventilation and equipment, and wear protective clothing as detailed in Section 8 Exposure Controls / Personal Protection and/or the product label.

Methods and Materials for Containment and Cleaning Up:

Restrict access to area of spill. Provide ventilation and protective clothing as required for the situation. Cover with dry lime or soda ash. Scrape up liquid coating with cardboard or rag and place in a closed container.

Environmental Precautions:

Review local, regional and/or national regulations for disposal. Silicone wastes can often be incinerated in approved facilities. Solid waste can often be sent to designated landfill sites.

## 7. Handling and Storage

Precautions for Safe Handling:

KEEP OUT OF REACH OF CHILDREN. Prevent eating, drinking, tobacco use, and cosmetic application in areas where there is a potential for exposure to the material. Avoid breathing vapours. Wear full protective clothing and equipment as detailed in Section 8 Exposure Controls / Personal Protection. After work, rinse gloves and



ANTI-GRAFFITI PROTECTIVE COATING

Issue Date (D/M/Y): DRAFT - 05/11/2018 Replaces (D/M/Y): 16/08/2015

Page 4 of 10

remove protective equipment, and wash hands thoroughly with soap and water after handling, and before eating, tobacco use, drinking, applying cosmetics or using the toilet. Wash contaminated clothing before reuse and separate from household laundry.

Conditions for Safe Storage, Including any Incompatibilities:

Store in cool dry conditions. Keep container tightly sealed when not in use. Protect product and contaminated materials from uncontrolled release into the environment, or from access by animals, birds or unauthorized people. Clean up spilled material immediately.

Specific End Use:

SAFETY DATA SHEET

Polysilioxane coating.

## 8. Exposure Controls / Personal Protection

Control Parameters:

Chemical Name	CAS No.	Exposure Limits
Butan-2-one-O,O',O"- (methylsilylidine)trioxime	22984-54-9	No assigned exposure limits.
Butan-2-one-O,O',O"- (vinylsilylidine)trioxime	2224-33-1	No assigned exposure limits.
3-aminopropyl triethoxysilane	919-30-2	No assigned exposure limits.
Octamethylcyclotetrasiloxane	556-67-2	10 ppm ACGIH TLV
Methyl Ethyl Ketoxime (MEKO)**	96-29-7	Workplace environmental exposure level: 10 ppm, AIHA

STEL = short-term exposure limit; TLV = threshold limit value.

- \* Component(s) are bound in the formulation and are not an exposure concern in the mixture or cured product.
- \*\* Methyl Ethyl Ketoxime (MEKO) is a curing by-product that is released when the coating comes in contact with humid air. It is recommended to keep workplace exposure levels below 3 ppm.

## Appropriate Engineering Controls:

If necessary, ensure work areas have adequate ventilation, containment, and procedures sufficient to maintain airborne levels below the TLV. Provide separate washing/shower and eating facilities.

#### Individual Protection Measures:

- General: Avoid breathing dusts, vapours or aerosols. Avoid contact with eye, skin and clothing. Wash thoroughly after handling, and before eating, drinking, applying cosmetics or handling tobacco.
- Eye/Face Protection: Safety glasses / chemical splash goggles.
- Skin Protection: Impervious gloves, coveralls and/or aprons may be useful to prevent contamination of skin and clothing. Choose gloves to protect hands against chemicals depending on the concentration specific to the place of work. Breakthrough time is not determined for the product. Change gloves often. We recommend clarifying the resistance of chemicals to protective gloves with the glove manufacturer. Wash hands before breaks and at the end of the workday.
- Respiratory Protection: General and local exhaust ventilation is recommended to maintain vapour exposures below the recommended limits. Where concentrations are unknown or are above the recommended limits, a NIOSH/MSHA approved respirator with an organic vapour cartridge should be used. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Environmental Exposure Refer to sections 6 and 12.



ANTI-GRAFFITI PROTECTIVE COATING

Vapour Pressure: Negligible at 25 °C.

Solubility(ies): Water - insoluble. Soluble in most

organic solvents.

Partition Coefficient (n-octanol/water): x

Explosive Properties: Not applicable.

Oxidizing Properties: Not applicable.

Auto-Ignition Temperature: Not applicable.

Decomposition Temperature: Not available.

Vapour Density: Not applicable.

Relative Density: 0.99

Viscosity: 2,000 ± 1,000 cP

VOC Content: 53 g/L

Issue Date (D/M/Y): DRAFT - 05/11/2018 Replaces (D/M/Y): 16/08/2015

SAFETY DATA SHEET

Page 5 of 10

Controls:

## 9. Physical and Chemical Properties

Appearance: Smooth, viscous liquid. Odour: Almost odourless. Odour Threshold: Not available. pH: Not available. Melting Point: Not applicable. Freezing Point: Not applicable. Initial Boiling Point: Not available. Boiling Point Range: Not available. Flash Point: 88 °C PMCC, ASTM D-93 Evaporation Rate: Not applicable. Flammability: Not applicable.

Upper/Lower Flammability Limits: Not applicable.

10.Stability and Reactivity

Reactivity:

Not reactive under normal use and storage conditions.

Stability:

Stable under normal use and storage conditions.

Possibility of Hazardous Reactions:

During a fire, irritating and possibly toxic gases may be generated by thermal decomposition or combustion.

Conditions to Avoid:

Temperatures above the flash point.

Incompatible Materials:

Strong oxidizers. Concentrated acids or bases cause degradation of polymer. Boiling water may soften and weaken material.

Hazardous Decomposition Products:

Combustion will produce carbon dioxide, carbon monoxide, silicon dioxide and nitrogen oxides. A component of this product can generate formaldehyde at approximately 150 °C and above in the atmosphere containing oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant and potential carcinogen.

## **11.Toxicological Information**

Relevant routes of exposure:

	Acute Effects	Chronic Effects
Inhalation	Not normally an inhalation hazard. At high vapour concentrations, curing by- product has a narcotic action with reversible effects.	Prolonged exposure to high vapour concentrations of curing by-product can cause headache, nausea, central nervous system depression, anesthesia and dizziness.
Ingestion	Very low toxicity. May cause irritation and obstruction to gastro-intestinal tract.	Effects unknown.
Skin Contact	Mild irritation; may cause transient reddening of the skin.	Effects unknown.
Eye Contact	Moderate irritation. Can cause burns.	Effects unknown.
Other	Component is suspected of damaging fertility.	Component is suspected of damaging fertility.



ANTI-GRAFFITI PROTECTIVE COATING

Issue Date (D/M/Y): DRAFT - 05/11/2018 Replaces (D/M/Y): 16/08/2015

#### Octamethylcyclotetrasiloxane (D4):

Range finding reproductive studies were conducted (whole body inhalation, 70 days prior to mating, gestation and lactation), with D4. Rats were exposed to 70 and 700 ppm. In the 700 ppm group, there was a statistically significant reduction in mean litter size and in implantation sites. No D4 related clinical signs were observed in the pups and no exposure related pathological findings were found. A two-year, combined chronic/carcinogenicity study, during which rats were exposed to D4 by inhalation, data showed a statistically significant increase in a benign uterine tumour in female rats exposed at the highest level – a level much higher than the low levels that consumers or workers may encounter. An expert panel of independent scientists who reviewed the results of this research concur that the finding seen in the two-year study occurred through a biological pathway that is specific to the rat and is not relevant to humans. Therefore, this observed effect does not indicate a potential health hazard to humans. In developmental toxicity studies, rats and rabbits were exposed to D4 at concentrations up to 700 ppm and 500 ppm respectively. No teratogenic effects (birth defects) were observed in either study.

#### Acute Toxicity:

	,				
	Product	Butan-2-one-O,O',O"- (methylsilylidine) trioxime	Butan-2-one-O,O',O"- (vinylsilylidine) trioxime	3-aminopropyl triethoxysilane	Octamethylcyclo tetrasiloxane
No dat	a available.	LD50, oral, rat, >5,000 mg/kg.	No data available.	No data available.	LD50 oral, rat 4,800 mg/kg (OECD Guideline 401); LC50 inhalation, rat, 4hr. > 12.1 mg/kg; LC50 inhalation, rat, 4hr., 36 mg/L (OECD Guideline 403)
Skin Irritat	tion:				
	Product	Butan-2-one-O,O',O"- (methylsilylidine) trioxime	Butan-2-one-O,O',O"- (vinylsilylidine) trioxime	3-aminopropyl triethoxysilane	Octamethylcyclo tetrasiloxane
cause t	ritation; may transient ing of the skin.	Sensitization possible. Irritates the skin.	Sensitization possible. Irritates the skin.	Irritant for skin and mucous membranes.	Non-irritating to the skin, rabbit (OECD Guideline 404)
Eye Irritati	ion:				
	Product	Butan-2-one-O,O',O"- (methylsilylidine) trioxime	Butan-2-one-O,O',O"- (vinylsilylidine) trioxime	3-aminopropyl triethoxysilane	Octamethylcyclo tetrasiloxane
	ate irritation. use burns.	Irritates the eyes.	Irritates the eyes.	Irritant effect.	Non-irritating to the eyes, rabbit (OECD Guideline 405).
Mutagenic	ity:				
	Product	Butan-2-one-O,O',O"- (methylsilylidine) trioxime	Butan-2-one-O,O',O"- (vinylsilylidine) trioxime	3-aminopropyl triethoxysilane	Octamethylcyclo tetrasiloxane
No adv anticip	erse effects ated.	No data available.	No data available.	No data available.	Negative, in vitro, Salmonella typhimuriun (OECD Guideline 471); Negative, in vitro, Mous Lymphoma Assay (OECI guideline 476); Negativ in vivo, Micronucleus test, (OECD Guideline 453)
Carcinoge	nicity:				
	Product	Butan-2-one-O,O',O"- (methylsilylidine)	Butan-2-one-O,O',O"- (vinylsilylidine)	3-aminopropyl triethoxysilane	Octamethylcyclo tetrasiloxane



# Si-COAT<sup>®</sup> 532<sup>™</sup> REMARKABLE<sup>®</sup> LOW VOC SPRAY GRADE ANTI-GRAFFITI PROTECTIVE COATING

Issue Date (D/M/Y): DRAFT - 05/11/2018 Replaces (D/M/Y): 16/08/2015

Page 7 of 10

	trioxime	trioxime		
No adverse effects anticipated.	No data available.	No data available.	No data available.	Inhalation, rat-female, 24 months, 150 mg/kg, NOAEC (OECD Guideline 453); Inhalation, rat- male, 24 months, >700 mg/kg, NOAEC (OECD Guideline 453).
eproductive Toxicity:				

## **Reproductive Toxicity:**

	Product	Butan-2-one-O,O',O"- (methylsilylidine) trioxime	Butan-2-one-O,O',O"- (vinylsilylidine) trioxime	3-aminopropyl triethoxysilane	Octamethylcyclo tetrasiloxane
	No data available.	No data available.	No data available.	No data available.	Rat, inhalation, 300 mg/kg, NOAEL parents (OECD Guideline 416); Rat, inhalation, 300 mg/kg, NOAEL F1 (OECD Guideline 416).
Te	ratogenicity:				
	Product	Butan-2-one-O,O',O"- (methylsilylidine) trioxime	Butan-2-one-O,O',O"- (vinylsilylidine) trioxime	3-aminopropyl triethoxysilane	Octamethylcyclo tetrasiloxane
	No adverse effects anticipated.	No data available.	No data available.	No data available.	Rabbit, inhalation, 18

## Specific Target Organ Toxicity (STOT) - Single Exposure:

Product	Butan-2-one-O,O',O"- (methylsilylidine) trioxime	Butan-2-one-O,O',O"- (vinylsilylidine) trioxime	3-aminopropyl triethoxysilane	Octamethylcyclo tetrasiloxane
No data available.	No data available.	No data available.	No data available.	No data available.
Specific Target Organ	Toxicity (STOT) – Repe	ated Exposure:		
Product	Butan-2-one-O,O',O"- (methylsilylidine) trioxime	Butan-2-one-O,O',O"- (vinylsilylidine) trioxime	3-aminopropyl triethoxysilane	Octamethylcyclo tetrasiloxane
No data available.	May cause damage to organs though prolonged or repeated exposure. Affected organs: cardiovascular/ hematological (hematopoiesis).	May cause damage to organs though prolonged or repeated exposure. Affected organs: cardiovascular/ hematological (hematopoiesis).	No data available.	No data available.
Aspiration Hazard:				
Product	Butan-2-one-O,O',O"- (methylsilylidine) trioxime	Butan-2-one-O,O',O"- (vinylsilylidine) trioxime	3-aminopropyl triethoxysilane	Octamethylcyclo tetrasiloxane
No data available.	No data available.	No data available.	No data available.	No data available.
Chronic Toxicity:				
Product	Butan-2-one-O,O',O"- (methylsilylidine) trioxime	Butan-2-one-O,O',O"- (vinylsilylidine) trioxime	3-aminopropyl triethoxysilane	Octamethylcyclo tetrasiloxane

All trademarks registered. Al rights reserved.



## Si-COAT<sup>®</sup> 532<sup>™</sup> REMARKABLE<sup>®</sup> LOW VOC SPRAY GRADE **ANTI-GRAFFITI PROTECTIVE COATING**

Issue Date (D/M/Y): DRAFT - 05/11/2018 Replaces (D/M/Y): 16/08/2015

Page 8 of 10

Potential for pulmonary edema, dermatitis.	No data available.	No data available.	No data available.	Inhalation, rat, 150 mg/kg, 24 months, NOAEC (OECD Guideline 453); Dermal, rabbit, 3 weeks, NOAEL (OECD Guideline 410)

NOTE: Curing by-product, methylethylketoxime (MEKO); male rats and mice exposed to MEKO throughout their lifetime developed liver tumours. Many commonly used chemicals cause liver tumours in rats and mice. The relevance to humans is unknown.

## **12.Ecological Information**

## **Ecotoxicity - Acute:**

Product	Butan-2-one-O,O',O"- (methylsilylidine) trioxime	Butan-2-one-O,O',O"- (vinylsilylidine) trioxime	3-aminopropyl triethoxysilane	Octamethylcyclo tetrasiloxane
No data available.	No data available.	No data available.	No data available.	LC50, 96h, Oncorhynchus mykiss, ≥0.022 mg/L EC50, 48h, Daphnia magna, >0.015 mg/L
cotoxicity - Chronic:				
Product	Butan-2-one-O,O',O"- (methylsilylidine) trioxime	Butan-2-one-O,O',O"- (vinylsilylidine) trioxime	3-aminopropyl triethoxysilane	Octamethylcyclo tetrasiloxane
No data available.	No data available.	No data available.	No data available.	NOEC, 93d, Oncorhynchus mykiss, ≥0.0044 mg/L; NOEC, 21d, Daphnia magna, 0.0079 mg/L; EC50, 96h, Selenastrum capricornatum, >0.022 mg/L.
ersistence and Degrad	ability:			
Product	Butan-2-one-O,O',O"- (methylsilylidine) trioxime	Butan-2-one-O,O',O"- (vinylsilylidine) trioxime	3-aminopropyl triethoxysilane	Octamethylcyclo tetrasiloxane
No data available.	No data available.	No data available.	No data available.	Not biodegradable.
ioaccumulative Potent	ial:			
Product	Butan-2-one-O,O',O"- (methylsilylidine) trioxime	Butan-2-one-O,O',O"- (vinylsilylidine) trioxime	3-aminopropyl triethoxysilane	Octamethylcyclo tetrasiloxane
No data available.	No data available.	No data available.	No data available.	Bioaccumulating.
lobility in Soil:				
Product	Butan-2-one-O,O',O"- (methylsilylidine) trioxime	Butan-2-one-O,O',O"- (vinylsilylidine) trioxime	3-aminopropyl triethoxysilane	Octamethylcyclo tetrasiloxane
No data available.	No data available.	No data available.	No data available.	No data available.
Other Adverse Effects:				
Product	Butan-2-one-O,O',O"- (methylsilylidine) trioxime	Butan-2-one-O,O',O"- (vinylsilylidine) trioxime	3-aminopropyl triethoxysilane	Octamethylcyclo tetrasiloxane

All trademarks registered. Al rights reserved.

SAFETY DATA SHEET

## Si-COAT<sup>®</sup> 532<sup>™</sup> REMARKABLE<sup>®</sup> LOW VOC SPRAY GRADE **ANTI-GRAFFITI PROTECTIVE COATING**

Issue Date (D/M/Y): DRAFT - 05/11/2018 Replaces (D/M/Y): 16/08/2015

Page 9 of 10

## **13.Disposal Considerations**

Product and Packaging Disposal:

Dispose in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

## **14.Transport Information**

**Transport Information** 

	Land Transport (ADR/RID)	Water Transport (ADN/ IMDG)	Air Transport (IATA-DGR)
UN Number			
UN Proper Shipping Name			
Transport Hazard Class			
Packing Group			
Environmental Hazards			
Special Precautions for Use	r:		
Not applicable.			
Transport in Bulk According	g to Annex II of Marpol 73/78 a	nd the IBC Code:	
Not available.			
15.Regulatory Informa	ation		
EU Regulations			
REACH - Candidate Lis	t of Substances of Very High Co	oncern for Authorization:	
Contains le: Dodecamethyl	ss than 1% of Octamet cyclohexasiloxane.	hylcyclotetrasiloxane, Decame	thylcyclopentasiloxane and
Regulation (EC) No. 64	9/2012 Import and Export of D	angerous Chemicals:	
Not applicabl	e.		
Regulation (EC) No. 10	05/2009 Substances that Deple	ete the Ozone Layer:	
Not applicabl	e.		
Regulation (EC) No. 85	0/2004 Persistent Organic Poll	utants:	
Not applicabl	e.		
Seveso III - Directive 2	012/18/EU Control of Major Ac	cident Hazards involving Dang	erous Substances:
Not applicabl	e.		
The ingredients of this pr	oduct are reported in the foll	owing inventories:	
AICS (Australia)	On or in compliance with the	-	
DSL (Canada)	On or in compliance with the	e inventory.	
ENCS/ISHL (Japan)	On or in compliance with the		
IECSC (China)	On or in compliance with the		
KECI (Korea)	On or in compliance with the	e inventory.	
NZIOC (New Zealand)	On or in compliance with the	•	
PICCS (Philippines)	On or in compliance with the		
REACH (European Unio	n) On or in compliance with the	e Inventory.	
TSCA (USA)	On or in compliance with the	e inventory.	
Other Regulations			
The regulatory info	rmation is not intended to be	e comprehensive. Other regu	ulations may apply to this

material.



ANTI-GRAFFITI PROTECTIVE COATING

Issue Date (D/M/Y): DRAFT - 05/11/2018 Replaces (D/M/Y): 16/08/2015

SAFETY DATA SHEET

Page 10 of 10

## Chemical Safety Assessment:

A chemical safety assessment has not been completed on this mixture.

## **16.Other Information**

Issue Date (D/M/Y):	05/11/2018
Replaces (D/M/Y):	16/08/2015

Abbreviations & Acronyms:

All abbreviations and acronyms have been fully defined in the relevant sections of the SDS.

Indication of changes:

Not applicable.

#### References

Sources of data used in the compilation of this safety data sheet (SDS) include, but are not limited to the following: internal technical data; data from raw material supplier MSDSs/SDSs, OECD eChem Portal search results; and European Chemicals Agency (ECHA) Chemical Property portal search results.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information provided is designed only as guidance for safe handling, use, processing, storage, transportation, and release and is not considered a warranty or product specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

It is the responsibility of persons in receipt of this product Safety Data Sheet (SDS) to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product.

All information and instructions provided in this Safety Data Sheet are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. CSL Silicones shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

This Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local CSL Silicones supplier a SDS applicable to the country in which the product is sold or intended to be used. Please note that the appearance and contents of the SDS may vary, even for the same product, between different countries, reflecting the compliance requirements.